

Corner Low Beam **ON**

No dark corner

Corner Low Beam **OFF**

Dark corner

LED COMBINATION HEADLIGHT 7 in 1

UR-1B001HL

Functions, Homologation

Functions	: Low Beam, Corner Low Beam, High Beam, Turn Light, Side DI, Parking, De-icing ECE R112, R6, R7, R10
Homologations	: DOT FMVSS108/SAE J914/SAE J588/SAE J222

Optical & Electric Features

LED Type	: OSRAM OEM Vehicle Level LEDs
Emitting color	: White and Amber (Turn)
Color Temp	: 5700K (White)
Energy Consumption (tested)	: Low Beam 35W; High Beam 21W; Corner Low Beam: 11W; Turn Light & Side DI: 2.7W; Parking: 0.5W
Current Draw @ 12V: (tested)	: Low Beam 2.91A; High Beam 1.75A; Corner Low Beam: 0.92A; Turn Light & Side DI: 0.225A;
Effective Lumen	: Parking Light: 0.04A Low Beam: 1040LM (OSRAM LED) High Beam: 1160LM (5530 LED) Corner Low Beam: 560LM; Turn Light & Side DI: 210LM; (Amber) Parking 24LM;

De-icing features

De-Icing Tech	: URSA's patented Replaceable Modular
De-icing Power	: 60W
Control Mode	: Automatic temp. sensor switch

Electromagnetic Features

EMC Grade	: CISPR 25 Class 5
Operating Voltage	: 10~30VDC
Connector	: 6 pin DT connector

Mechanical Features

Size	: 230X158X116mm
Housing Material	: Aluminium Alloy
Lens Material	: Anti-UV PC
Lens Process	: Surface Hardened
PC Brand	: COVESTRO 2407
Bracket Material	: Tough 304 Stainless Steel
Anti-Corrosion	: ISO 9227 240H
Vibration Level	: 15.3Grms
IP Rate	: IP66, IP6K9K
Work Temp	: -40~+50°C

So this is Life

Life Time	: >30,000h
-----------	------------

