

LED COMBINATION HEADLIGHT 8 in 1

UR-1B002CMB

Functions, Homologation

Functions	: Low Beam; High Beam; Corner Low Beam; De-icing; Auxiliary Low Beam; Parking; Turn Light; Side DI;
Homologations	: ECE R112, R6, R7, R10 DOT J1383/ J914/ J588 SAE J582/ J222

Optical & Electric Features

LED Type	: OSRAM OEM Vehicle Level LEDs
Emitting color	: White and Amber (Turn)
Color Temp	: 5700K (White)

Energy Consumption

Low Beam: 35.5W;	High Beam: 24.5W ;
Corner Low Beam: 10.5W	Auxiliary Low Beam: 4.5W
Parking: 0.5W	Turn Light: 5W Side DI: 2.5W

Current Draw @ 12V:

Low Beam: 2.95A	High Beam: 2.04A
Corner Low Beam: 0.87A	Auxiliary Low Beam: 0.375A
Parking: 0.04A	Turn Light: 0.417A Side DI: 0.208A

Raw Lumen:

Low Beam: 2800LM	High Beam: 5750LM
Corner Low Beam: 1200LM	Auxiliary Low Beam: 1550LM
Parking: 187LM	Turn Light: 540LM Side DI: 270LM

Effective Lumen:

Low Beam: 1008.6LM	High Beam: 1196LM
Corner Low Beam: 520.7LM	Auxiliary Low Beam: 570LM
Parking: 18.3LM	Turn Light: 210LM Side DI: 104LM

URSA's Patented De-icing Technology

De-Icing Tech	: Heating Glass
De-icing Power	: 20W
Control Mode	: Temp. Sensor @ constant temp.
Heating Temp	: Constant 45°C lens

Electromagnetic Features

EMC Grade	: CISPR 25 Class 3
Operating Voltage	: 10~30VDC
Connector	: 6 pin DT connector

Mechanical Features

Size	: 212X163.5X104mm
Housing Material	: Aluminium Alloy
Lens Material	: Tempered Glass
Work Temp	: -40~+50°C

So this is Life

Life Time	: >30,000H
-----------	------------

